

EXAMPLE OSCAM READERS

WILLO3092

EACH SEPARATE LINE NEEDS 1 READER – IF YOU HAVE 5 LINES, YOU NEED 5 READERS

EXAMPLES OF CCCAM AND NEWCAMD LINES BELOW – YOU ONLY NEED TO CHANGE THE HIGHLIGHTED PARTS

LEAVE THE COMMA IN BETWEEN SERVER AND PORT

SATELLITE C LINE

```
[reader]
label = sky-cline-server
protocol = cccam
device = server,port
user = username
password = password
inactivitytimeout = 30
group = 1
cccversion = 2.3.2
```

SATELLITE N LINE

```
[reader]
label = sky-nline-server
protocol = newcamd
device = server,port
key = 0102030405060708091011121314
user = username
password = password
connectoninit = 1
group = 1
```

CABLE C LINE

```
[reader]
label= vm-cline-server
enable=1
protocol=cccam
device = server,port
user = username
password = password
cccversion=2.1.2
group=1
inactivitytimeout=1
reconnecttimeout=30
lb_weight=100
cccmaxhops=10
```

CABLE N LINE

```
[reader]
label = vm-nline-server
protocol = newcamd
device = server,port
key = 0102030405060708091011121314
user = username
password = password
disableserverfilter = 1
connectoninit = 1
caid = 1841
ident =
1841:000000,005b01,005a01,005b02,005
b03
group = 1
```